

SS-ISO 2768-1

LINEAR MEASURES

SS-ISO 2768-1

Values in mm

Tolerance Class		Permissible deviations for basic size range							
Designation	Description	0,5)1 up to	over 3	over 6	over 30	over 120	over 400	over 1000	over 2000
		3	up to 6	up to 30	up to 120	up to 400	up to 1000	up to 2000	up to 4000
		±	±	±	±	±	±	±	±
f	fine	0,05	0,05	0,10	0,15	0,20	0,30	0,50	–
m	medium	0,10	0,10	0,20	0,30	0,50	0,80	1,20	2,00
c	coarse	0,20	0,30	0,50	0,80	1,20	2,00	3,00	4,00
v	very coarse	–	0,50	1,00	1,50	2,50	4,00	6,00	8,00

1) For nominal sizes below 0,5 mm, the deviations shall be indicated adjacent to the relevant nominal sizes

BROKEN EDGES

SS-ISO 2768-1

Tolerance Class		Permissible deviations for basic size range		
Designation	Description	0,5)1 up to	over 3	over 6
		3	up to 6	up to 30
		±	±	±
f	fine			
m	medium	0,20	0,50	1,00
c	coarse			
v	very coarse	0,40	1,00	2,00

1) For nominal sizes below 0,5 mm, the deviations shall be indicated adjacent to the relevant nominal sizes